beyma

PROFESSIONAL LOUDSPEAKERS
www.beyma.com

CD-320Fe/Ti

COMPRESSION DRIVER

Preliminary Data Sheet

KEY FEATURES

- Next generation high performance 2” (50,8 mm) exit compression driver
- Deplocex® Patent Pending Technology for improved thermal disipation, low power compression losses and high power handling
- 3” (76,2 mm) Copper Clad Aluminum voice coil with Nomex former
- 260 W program power above 1,2 kHz
- Sensitivity: 110 dB (1W / 1m)
- Exclusive Titanium dome and surround design optimized with F.E.M for linear and extended response with minimized resonances
- Copper shorting cap for reduced distortion, linear inductance and increased output
- Propietary design of metal alloy phase plug with F.E.M optimized geometry and improved assembly design
- F.E.M. optimized ceramic magnetic circuit
- Aluminium cover





TECHNICAL SPECIFICATIONS

Throat diameter	50,8 mm	2 in
Rated impedance		8 Ω
Minimum impedance		5,8 Ω
D.C. resistance		4,4 Ω
Power capacity [1]	90 W_{AES} above 0,8 kHz	
	130 W_{AES} above 1,2 kHz	
Program power [2]	180 W above 0,8 kHz	
	260 W above 1,2 kHz	
Sensitivity [3]	110 dB 1W / 1m @ Z_N	
	coupled to 50°x 50° horn	

Frequency range	0,5 - 18 kHz	
Recommended crossover	0,8 kHz or higher	
	(12 dB/oct min.)	
Voice coil diameter	76,2 mm	3 in
Flux density		1,8 T
Bl factor		9,5 N/A

Notes:

[1] The power capaticty is determined according to AES2-1984 (r2003) standard.

[2] Program power is defined as the transducer’s ability to handle normal music program material.


[3] Sensitivity was measured at 1m distance, on axis, with 1W input, averaged in the range 1 - 7 kHz

beyma

PROFESSIONAL LOUDSPEAKERS
www.beyma.com

CD-320Fe/Ti

COMPRESSION DRIVER
Preliminary Data Sheet




Note: On axis frequency response measured coupled to 50°x 50° horn in anechoic chamber, 1W / 1m

MOUNTING INFORMATION

Overall diameter	165 mm	6,5 in
Depth	97 mm	3,82 in
Mounting	Four M6 threaded holes, 90º apart on 101,6 mm (4 in) diameter circle	
Net weight	5,8 kg	12,8 lb
Shipping weight	6 kg	13,2 lb

DIMENSION DRAWING



Acústica Beyma SL - P.I. Moncada II, C/ Pont Sec, 1C - 46113 Moncada, Valencia (Spain) - Tel. +34 96 130 13 75 - beyma@beyma.com

10/24