beyma

PROFESSIONAL LOUDSPEAKERS
www.beyma.com


SMC-65Nd

COMPRESSION DRIVER

KEY FEATURES

- 1,4” exit (36 mm) high frequency compression driver
- 2,8” (72,2 mm) voice coil diameter
- 140 W program power above 1.5 kHz
- Sensitivity: 108 dB, 1W / 1m
- Shorting copper cap for extended response
- Titanium dome with polyester surround
- Lightweight aluminium voice coil
- Neodymium magnet





TECHNICAL SPECIFICATIONS

Nominal diameter	36 mm	1,4 in
Rated impedance		8 Ω
Minimum impedance		7,5 Ω
D.C. resistance		5,5 Ω
Power capacity [1]	50 W_{AES} above 0,8 kHz	
	70 W_{AES} above 1,5 kHz	
Program power [2]	100 W above 0,8 kHz	
	140 W above 1,5 kHz	
Sensitivity [3]	108 dB 1W / 1m @ Z_N	
	coupled to TD-385	

Frequency range	0,6 - 20 kHz	
Recommended crossover	0,8 kHz or higher	
	(12 dB/oct min.)	
Voice coil diameter	72,2 mm	2,8 in
Magnetic assembly weight	2,1 kg	4,6 lb
Flux density		2 T
Bl factor		11,3 N/A

Notes:

[1] The power capaticty is determined according to AES2-1984 (r2003) standard.

[2] Program power is defined as the transducer’s ability to handle normal music program material.

[3] Sensitivity was measured at 1m distance, on axis, with 1W input, averaged in the range 1 - 7 kHz

Acústica Beyma SL - P.I. Moncada II, C/ Pont Sec, 1C - 46113 Moncada, Valencia (Spain) - Tel. +34 96 130 13 75 - beyma@beyma.com


beyma

PROFESSIONAL LOUDSPEAKERS

www.beyma.com

SMC-65Nd

COMPRESSION DRIVER



Note: On axis frequency response measured coupled to TD-385 horn in anechoic chamber, 1W / 1m

MOUNTING INFORMATION

Overall diameter	123 mm	4,8 in
Depth	53 mm	2,1 in
Mounting	Four M6 threaded holes, 90º apart on 101,6 mm (4 in) diameter circle	
Net weight	2,2 kg	4,8 lb
Shipping weight	2,7 kg	5,9 lb

DIMENSION DRAWING

