HF Compression Drivers

CDX1-1070



1-inch exit ferrite magnet compression driver

- Single piece PETP diaphragm and surround
- 2,200 Hz recommended min. crossover freq (12dB/oct)

24W
Continuous power rating

106dB
Sensitivity

1-inch
Copper clad aluminium voice coil

General Specifications

Power Rating	12W
Continuous power rating	24W
Rated impedance	8 ohm
Sensitivity	106dB
Frequency range	1500-20,000Hz
Recommended min. crossover (12 dB/oct)	2200Hz
Magnet type	Ferrite
Voice coil diameter	25mm / 1in
Voice coil material	Copper clad aluminium
Diaphragm material	PETP film
Surround material	PETP film

Mounting Information

Width	70mm / 2.8in
Depth	50mm / 2in
Fitting	Bolt (2 x M6 holes on 76mm/3in PCD)
Throat exit	25mm / 1in
Unit weight	0.7kg / 1.5lb


Packed Dimensions & Weight

Single pack size W x D x H	98mm x 98mm x 77mm / 3.8in x 3.8in x 3.0in
Single pack weight	1.0kg / 2.2lb

Horns

T5359	H19040P Horn
T5134	H17050 No Bell Horn

Frequency Response and Impedance Curves



Celestion, Claydon Business Park, Great Blakenham, Ipswich, IP6 0NL United Kingdom