HF Compression Drivers

CDX1-1770



1-inch exit ferrite magnet compression driver

- Single piece PETP diaphragm and surround
- Next generation Sound Castle soft clamping diaphragm assembly
- 2,000Hz recommended min. crossover freq (12dB/oct)

80W
Continuous power rating

108dB
Sensitivity

1.75in
Copper clad aluminium voice coil

General Specifications

Power Rating	40W
Continuous power rating	80W
Rated impedance	8 ohm
Sensitivity	108dB
Frequency range	1400Hz-20kHz
Recommended min. crossover (12 dB/oct)	2200Hz
Magnet type	Ferrite
Voice coil diameter	44mm / 1.75in
Voice coil material	Copper clad aluminium
Diaphragm material	PETP film
Surround material	PETP film


Mounting Information

Width	100mm / 4in
Depth	55.6mm / 3.94in
Fitting	Bolt (2/3 M6 holes on 76/57mm, 3 .0/2 .24in PCD)
Throat exit	25mm / 1in
Unit weight	1.36kg / 3lb

Packed Dimensions & Weight

Multi pack qty	16
Multi pack size W x D x H	495mm x 495mm x 90mm / 19.5in x 19.5in x 3.5in
Multi pack weight	25.5kg / 56lb

Frequency and Response and Impedance Curves



Celestion, Claydon Business Park, Great Blakenham, Ipswich, IP6 0NL United Kingdom