EMINENCE®

The Art and Science of Sound

Redcoat Guitar **12”**

THE GOVERNOR™

The Eminence Governor guitar speaker is the natural upgrade for the classic American amp. A versatile guitar speaker, great for southern rock or blues. Nice tight low-end, smooth midrange and top end sparkle. British cousin to Red White and Blues.



SPECIFICATION

Nominal Basket Diameter	12.0”, 305 mm
Nominal Impedance*	8 Ω
Power Rating**	75 W
Resonance (Fs)	101 Hz
Usable Frequency Range	80 Hz – 4.2 kHz
Sensitivity***	102.3 dB
DC Resistance (Re)	6.81 Ω
Magnet Weight	56 oz.
Gap Height	.312”, 7.9 mm
Voice Coil Diameter	1.75”, 44 mm


MOUNTING INFORMATION

Enclosure Type	
Closed Back	Acceptable
Open Back	Acceptable
Overall Diameter	12.03”, 305.6 mm
Baffle Hole Diameter	11.07”, 281.2 mm
Depth	5.20”, 132.1 mm
Front Sealing Gasket	Yes
Rear Sealing Gasket	Yes
Mounting Holes Diameter	0.25”, 6.4 mm
Mounting Holes B.C.D.	11.59”, 294.4 mm
Net Weight	10.80 lbs , 4.90 kg
Shipping Weight	12.60 lbs , 5.72 kg

MATERIALS OF CONSTRUCTION

Copper voice coil
Nomex former
Ferrite magnet
Non-vented core
Pressed steel basket
Paper cone
Paper cone edge
Zurette dust cap

*FREQUENCY RESPONSE**







LEARN MORE AT EMINENCE.COM

* See footnotes on page 2 for information regarding nominal impedance, power rating and sensitivity.

EMINENCE®

The Art and Science of Sound

From design and manufacturing to the stage or studio. Once you've experienced the performance of Eminence, you'll never accept anything else.

MISSION STATEMENT

Eminence is dedicated to providing the best Quality, Value and Service to meet our customers' needs.

FOOTNOTES

* Please consult www.eminence.com for specifications of models with alternative impedances.

** Multiple units exceed published ratings evaluated under EIA 426A specification while tested in a free-air, non-temperature-controlled environment.

*** The average output across the usable frequency range when applying 1W/1m into the nominal impedance. i.e: 2.83V/8Ω, 4V/16Ω. Eminence response curves are measured under the following conditions: All speakers are tested at 1W/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2 ft. x 2 ft. baffle is built into the wall with the speaker mounted flush against a steel ring for minimum diffraction | Carver PM-120 amplifier | 2700 cu. ft. chamber with fiberglass on all six surfaces (three with custom-made wedges).

**** BETA 8CX, 10CX, and 12CX are coaxial speakers with tweeter sold separately. Published usable frequency response contingent upon use of ASD:1001 HF Driver.

***** Multiple units exceeded published ratings evaluated under EIA-426A or AES specification while mounted on Eminence's H290, H290S, or H2EA horn in a non-temperature-controlled environment.

******The average on axis output across the entire usable frequency range when applying 1W/1m into the nominal impedance, i.e. 2.83V/8Ω, 4V/16Ω. Eminence response curves are measured under the following conditions: All speakers are tested at 1W/1m using a variety of test set-ups for the appropriate impedance | LMS using 0.25" supplied microphone (software calibrated) mounted 1m from wall/baffle | 2ft x 2ft baffle is built into the wall with horn front mounted | Carver PM-120 amplifier | 2700 cu.ft. chamber with fiberglass on all six surfaces (three with custom-made wedges).

Prices, specifications and product cosmetics are subject to change without notice.

EMINENCE SPEAKER LLC

838 Mulberry Pike, Eminence, KY 40019

DESIGNED AND ASSEMBLED IN THE USA

Follow us:

EMINENCE.COM