faital PRO PROFESSIONAL LOUDSPEAKERS

10HX230



LF 10" - 250 W - 96 dB - 8 Ohm
HF 30 W - 107 dB - 8 Ohm

NOMINAL SPECIFICATIONS

Nom. Diameter	250 mm (10 in)
Overall Diameter	261 mm (10.28 in)
Bolt Circle Diameter	246 mm (9.69 in)
Baffle Cutout Diameter	230 mm (9.06 in)
Depth	136.5 mm (5.37 in)
Flange and Gasket Thickness	12 mm (0.47 in)
Net Weight	**5 kg (11.0 lb)**
Shipping Box (Single Carton Box)	282 x 280 x 140 mm (9.3 x 9.3 x 6.1 in)
Shipping Weight	5.4 kg (11.9 lb)

PART NUMBER

Push Terminals - 8 Ohm Version	02504277
Recone Kit LF - 8 Ohm Version	R2504277
Recone Kit HF - 8 Ohm Version	R0374049

TECHNICAL PARAMETERS


	LF	HF
Nom. Impedance	8 Ohm	8 Ohm
Minimum Impedance	6.4 Ohm	6.9 Ohm
AES Power Handling **(1)**	250 W	30 W
Max Power Handling (2)	**500 W**	**60 W**
Sensitivity (1W/1m) (3)	**96 dB**	**107 dB**
Frequency Range	65÷4000 Hz	1500÷20000 Hz
Voice Coil Diameter	**65 mm (2.56 in)**	**37 mm (1.46 in)**
Winding Material	**Al**	**Al**
Former Material	Glass Fiber	Kapton
Winding Depth	17.4 mm (0.69 in)	2.1 mm (0.08 in)
Magnetic Gap Depth	**8 mm (0.31 in)**	**2.6 mm (0.10 in)**
Flux Density	1.15 T	1.85 T
Min. Cross. Freq. **(4)**	-	1.7 kHz
Dispersion Angle	-	110°
Diaphragm Material	**-**	**Ketone Polymer**
Diaphragm Shape	**-**	**Annular**
Magnet	Ferrite Ring	Neodymium Ring
Basket Material	Aluminum	-
Demodulation	Aluminum Ring	-
Cone Surround **(5)**	Triple Roll	-
NET Air Volume filled by Loudspeaker	1.5 dm^3 (0.053 ft^3)	-
Spider Profile	1x variable height waves	-


THIELE & SMALL PARAMETERS


Fs	65 Hz
Re [LF]	5.3 Ohm
Re [HF]	5.5 Ohm
Qes	0.42
Qms	5.8
Qts	0.39
Vas	30.5 dm^3 (1.08 ft^3)
Sd	347 cm^2 (53.71 in^2)
Xmax **(6)**	7.37 mm
Xdamage **(7)**	14.8 mm
Mms	33.0 g
Bl	13.1 N/A
Le	0.54 mH
Mmd	25.7 g
Cms	0.18 mm/N
Rms	2.4 kg/s
Eta Zero	1.95 %
EBP	155 Hz


NOTES:

(1) 2 Hours Test According to AES 2-1984 Rev. 2003
(2) Maximum power is defined as 3dB greater than nominal power.
(3) HF Sensitivity averaged within the frequency range
(4) 12 dB/oct or higher slope high-pass filter
(5) Treated Polycotton
(6) Xmax= [(winding depth - magnetic gap depth)/2] + (magnetic gap depth/3)
(7) Maximum excursion before permanent damage









©Copyright 2026 **Faital S.p.A.** • All rights reserved.