PROFESSIONAL LOUDSPEAKERS

12XL1200

12" - 1400 W - 93 dB - 8 Ohm



NOMINAL SPECIFICATIONS

Nominal Diameter	300 mm (12 in)
Overall Diameter	316 mm (12.44 in)
Bolt Circle Diameter	298.5 mm (11.75 in)
Baffle Cutout Diameter	282 mm (11.10 in)
Depth	168.75 mm (6.64 in)
Flange and Gasket Thickness	12.45 mm (0.49 in)
Net Weight	**6.8 kg (15.0 lb)**
Shipping Box (Single Carton Box)	350 x 346 x 216 mm (13.8 x 13.6 x 8.5 in)
Shipping Weight	7.5 kg (16.5 lb)

PART NUMBER

Push Terminals - 8 Ohm Version	03004310
Recone Kit - 8 Ohm Version	R3004310

NOTES:

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3dB greater than nominal power.

(3) Treated Polycotton

(4) Xmax= [(winding depth - magnetic gap depth)/2] + (magnetic gap depth/3)


(5) Maximum excursion before permanent damage


TECHNICAL PARAMETERS


Nominal Impedance	8 Ohm
Minimum Impedance	6.5 Ohm
AES Power Handling **(1)**	1400 W
Maximum Power Handling (2)	**2800 W**
Sensitivity (1W/1m)	**93 dB**
Frequency Range	50÷2500 Hz
Voice Coil Diameter	**100 mm (4 in)**
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	28.9 mm (1.14 in)
Magnetic Gap Depth	**12 mm (0.47 in)**
Flux Density	1.1 T
Magnet	Neodymium Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround **(3)**	Triple Roll
NET Air Volume filled by Loudspeaker	2.9 dm^3 (0.102 ft^3)
Spider Profile	2x non-adjacent symmetrical variable height waves

THIELE & SMALL PARAMETERS

Fs	50 Hz
Re	5 Ohm
Qes	0.43
Qms	14.8
Qts	0.42
Vas	25.0 dm^3 (0.88 ft^3)
Sd	518 cm^2 (80.29 in^2)
Xmax **(4)**	12.45 mm
Xdamage **(5)**	24 mm
Mms	152 g
Bl	23.6 N/A
Le	1.3 mH
Mmd	138.7 g
Cms	0.07 mm/N
Rms	3.2 kg/s
Eta Zero	0.71 %
EBP	116 Hz







©Copyright 2026 **Faital S.p.A.** • All rights reserved.