PROFESSIONAL LOUDSPEAKERS

18HP1060

18" - 1200 W - 98 dB - 4 Ohm



NOMINAL SPECIFICATIONS

Nominal Diameter	460 mm (18 in)
Overall Diameter	460 mm (18.11 in)
Bolt Circle Diameter	440 mm (17.32 in)
Baffle Cutout Diameter	422 mm (16.61 in)
Depth	215 mm (8.46 in)
Flange and Gasket Thickness	13.9 mm (0.55 in)
Net Weight	**7.3 kg (16.1 lb)**
Shipping Box (Single Carton Box)	503 x 500 x 258 mm (19.8 x 19.7 x 10.2 in)
Shipping Weight	8.7 kg (19.2 lb)

PART NUMBER

Push Terminals - 4 Ohm Version	04604066
Recone Kit - 4 Ohm Version	R4604066

NOTES:


(1) 2 Hours Test According to AES 2-1984 Rev. 2003
(2) Maximum power is defined as 3dB greater than nominal power.
(3) Treated Polycotton
(4) Xmax= [(winding depth - magnetic gap depth)/2] + (magnetic gap depth/3)
(5) Maximum excursion before permanent damage


TECHNICAL PARAMETERS


Nominal Impedance	4 Ohm
Minimum Impedance	3.8 Ohm
AES Power Handling **(1)**	1200 W
Maximum Power Handling (2)	**2400 W**
Sensitivity (1W/1m)	**98 dB**
Frequency Range	35÷1600 Hz
Voice Coil Diameter	**100 mm (4 in)**
Winding Material	Cu
Former Material	Glass Fiber
Winding Depth	28.9 mm (1.14 in)
Magnetic Gap Depth	**12 mm (0.47 in)**
Flux Density	1.22 T
Magnet	Neodymium Ring
Basket Material	Aluminum
Demodulation	Aluminum Ring
Cone Surround **(3)**	Triple Roll
NET Air Volume filled by Loudspeaker	5.3 dm^3 (0.187 ft^3)
Spider Profile	2x non-adjacent symmetrical variable height waves

THIELE & SMALL PARAMETERS

Fs	35 Hz
Re	2.9 Ohm
Qes	0.34
Qms	13.3
Qts	0.33
Vas	184.4 dm^3 (6.51 ft^3)
Sd	1212 cm^2 (187.86 in^2)
Xmax **(4)**	12.45 mm
Xdamage **(5)**	21 mm
Mms	230.0 g
Bl	20.7 N/A
Le	1.09 mH
Mmd	182.3 g
Cms	0.09 mm/N
Rms	3.8 kg/s
Eta Zero	2.24 %
EBP	103 Hz







©Copyright 2026 **Faital S.p.A.** • All rights reserved.